LMPBSS84JZF 60V P-Channel MOSFET

Features

- -60V/-0.13A, $R_{DS(ON)}$<10Ω@V_{GS}=-5V
- Super high density cell design for extremely low RDS (ON)
- Exceptional on-resistance and maximum DC current capability
- SOT-23 package design

Product Description

LMPBSS84JZF, P-Channel enhancement mode MOSFET, uses Advanced Trench Technology to provide excellent $R_{DS(ON)}$, low gate charge.

These devices are particularly suited for low voltage power management, such as smart phone and notebook computer and other battery powered circuits, and low in-line power loss are needed in commercial industrial surface mount applications.

Applications

- DC to DC Converter
- Cellular & PCMCIA Card
- Power Management in Portable and Battery etc
- Cordless Telephone

Pin Configuration

LMPBSS84JZF (SOT-23)



PIN	Description
1	Gate
2	Source
3	Drain



Notice: The information in this document is subject to change without notice.

Ordering Information

Ordering Information					
Part Number	P/N	PKG code	Pb Free code	Package	Quantity
LMPBSS84JZF	LMPBSS84	JZ	F	SOT-23	3000

Marking Information

Marking Information		
Part Marking	Part Number	LFC code
PD	P	D

Absolute Maximum Ratings

(T_C=25ºC Unless otherwise noted)

Symbol	Parameter	Typical	Unit
V_{DSS}	Drain-Source Voltage	-60	V
V_{GSS}	Gate-Source Voltage	±20	V
I_D	Continuous Drain Current(T_A=25℃)	-130	mA
I_{DM}	Pulsed Drain Current (tp≦10us)	-520	mA
I_S	Continuous Current	-0.13	A
P_D	Power Dissipation (T_A=25ºC)	225	mW
T_J	Operating Junction Temperature	-55 to 150	ºC
T_{STG}	Storage Temperature Range	-55 to 150	ºC
$R_{\theta JA}$	Maximax Junction to Ambient	556	ºC/ W

Note 1: Pulse Test: PW≦300us, Duty Cycle≦2%.
2: Switching Time is Essentially Independent of Operating Temperature.

Notice: The information in this document is subject to change without notice.

Electrical Characteristics

(T_C=25ºC Unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}=0V,I_D=-250uA	-60			V
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS},I_D=-1.0mA	-0.8		-2.0	V
I_{GSS}	Gate-Source Leakage Current	V_{DS}=0V,V_{GS}=±20V			±60	uA
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}= -25V,V_{GS}=0V			-0.1	uA
		V_{DS}= -50V,V_{GS}=0V			-15	uA
$R_{DS(on)}$	Drain-Source On-Resistance	V_{GS}=-5V,I_D=-100mA			10	Ω
g_{fs}	Forward Transconductance	V_{DS}=-25V,I_D=-100mA, f=1.0KHz	50			mS
V_{SD}	Forward Voltage			-2.5		V
Dynamic						
C_{iss}	Input Capacitance	V_{DS}=-5V, V_{GS}=0V,f=1MHz		30		pF
C_{oss}	Output Capacitance			10		pF
C_{rss}	Reverse Transfer Capacitance			5.0		pF
Q_G	Gate Charge			6		nC
$t_{d(on)}$	Turn-On Time	V_{DD}=-15V, R_L=50Ω ,I_D=-2.5A		25		ns
t_r				1.0		ns
$t_{d(off)}$	Turn-Off Time			16		ns
t_f				8.0		ns

Typical Performance Characteristics



Transfer Characteristics



On-Region Characteristics

Notice: The information in this document is subject to change without notice.

Typical Performance Characteristics(continue)



On-Resistance versus Drain Current



On-Resistance versus Drain Current



On-Resistance Variation with Temperature



Gate Charge



Body Diode Forward Voltage

Notice: The information in this document is subject to change without notice.

Package Dimension:



Dimensions				
Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A	0.900	1.200	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.100	0.035	0.039
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0º	8º	0º	6º

Notice: The information in this document is subject to change without notice.

NOTICE:

LFC Semiconductor assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all LFC Semiconductor products described or contained herein. LFC Semiconductor products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. LFC Semiconductor makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Information furnished is believed to be accurate and reliable. However LFC Semiconductor assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of LFC Semiconductor. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information without express written approval of LFC Semiconductor.

Notice: The information in this document is subject to change without notice.